

What is claimed is:

Sub
A1
1. A method of data storage address translation, the ✓
method comprising:

5 receiving a first address in a first address space;
traversing a trie based on the first address; and
determining a second address based on the traversal.

10 2. The method of claim 1, wherein the first address has a
different address space than the second address.

3. The method of claim 2, wherein the first address has a
larger address space than the second address.

15 4. The method of claim 1, wherein the trie includes at
least one leaf identifying an address in the second address
space.

20 5. The method of claim 1, wherein the second address
comprises an address of a cache memory.

25 6. The method of claim 5, further comprising, based on the
traversal, determining whether the cache stores information
identified by the first address.

7. The method of claim 6, wherein the trie comprises a
multi-dimensional array, wherein an index of a dimension of the
array corresponds to different trie branches.

30 8. The method of claim 7, wherein traversing the trie
comprises, repeatedly, indexing into the dimension of the array
using a portion of the first address.

9. The method of claim 5, wherein the first address comprises an address of permanent data storage.

5 10. The method of claim 1, wherein traversing the trie based on the first address comprises performing an operation on the first address; and traversing the trie using the operation results.

10 11. The method of claim 1, wherein the second address associated with the first address dynamically changes.

12. A data storage system, comprising:
15 (a) a storage area having a first address space;
(b) a cache having a second address space; and ✓
(c) instructions for causing a processor to
(1) receive a first address in the first address
space;
(2) traverse a trie based on the first address; and
20 (3) determine a second address in the second address
space based on the traversal.

13. The data storage system of claim 12, wherein the instructions further comprise instructions for causing the
25 processor to determine whether the cache stores a block in the
storage area based on the trie traversal.

14. The data storage system of claim 12, wherein the
30 instructions for causing the processor to receive a first
address comprise instructions for causing the processor to
receive a first address included in a data access request
received from a host connected to the data storage system.

15. The data storage system of claim 12, wherein the instructions for causing the processor to traverse the trie based on the first address comprise instructions for causing the processor to:

perform an operation on the first address; and
traverse the trie using the operation results.

16. The data storage system of claim 12, wherein the second address associated with the first address dynamically changes.

17. A computer program product, disposed on a computer readable medium, for data storage address translation, the computer program including instructions for causing a processor to:

receive a first address within a first address space;
traverse a trie based on the first address; and
determine a second address based on the traversal.

18. The computer program of claim 17, wherein the first address has a different address space than the second address.

19. The computer program of claim 18, wherein the first address has a larger address space than the second address.

20. The computer program of claim 17, wherein the trie includes at least one branch identifying an address in the second address space.

21. The computer program of claim 17, wherein the second address comprises an address of a cache memory.

22. The computer program of claim 21, further comprising, instructions for causing the processor to, based on the traversal, determine whether the cache stores information identified by the first address.

5

23. The computer program of claim 17, wherein the trie comprises a multi-dimensional array, wherein an index of a dimension of the array corresponds to different trie branches.

10

24. The computer program of claim 17, wherein the first address comprises an address of permanent data storage.

25. The computer program of claim 17, wherein the instructions for causing the processor to traverse the trie comprise instructions for causing the processor to:
perform an operation on the first address; and
traverse the trie using the operation results.

26. The computer program of claim 17, wherein the second address associated with the first address dynamically changes.

27. A method of data storage address translation at a system having a storage area composed of different physical devices, a shared cache for caching blocks of data in the storage area, and connections to different host processors, the method comprising:

receiving a storage area address within a storage area address space based on a request received from one of the host processors;

traversing a trie based on the storage area address, the traversing identifying a trie leaf identifying a cache address in a cache address space; and

